



# SolarEdge Three Phase Inverters (South Korea)



## The best choice for SolarEdge enabled systems

- Superior efficiency (98%)
- Small, lightest in its class, and easy to install
- Built-in module-level monitoring
- Communication to internet via Ethernet or Wireless
- IP65 – Outdoor and indoor installation



*architects of energy™*



# Three Phase Inverters

SE10.5k-KOR - SE17k-KOR

All our solar inverters are part of SolarEdge's innovative system designed to provide superior performance at a competitive price. The SolarEdge PV inverter combines a sophisticated, cutting-edge digital control technology and a one stage, ultra-efficient power

conversion architecture to achieve superior performance – over 97% efficiency and best-in-class reliability. Our fixed-voltage technology ensures the inverter is always working at its optimal input voltage, regardless of the number of modules or environmental conditions.

## TECHNICAL DATA

	SE10.5k-KOR	SE12.5k-KOR	SE15k-KOR	SE16k-KOR	SE17k-KOR	
<b>OUTPUT</b>						
Rated AC Power Output	10500	12500	15000	16000	17000	VA
Maximum AC Power Output	10500	12500	15000	16000	17000	VA
AC Output Voltage - Line to Line / Line to Neutral (Nominal)	380 / 220					Vac
AC Output Voltage - Line to Neutral Range	193 - 264.5					Vac
AC Frequency	60 ± 5					Hz
Maximum Continuous Output Current (per Phase)	17	20	23	25.5	26	A
Residual Current Detector / Residual Current Step Detector	300 / 30					mA
Grids Supported - Three Phase	3 / N / PE ; 230 / 400					V
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes					
<b>INPUT</b>						
Recommended Maximum DC Power * (Module STC)	11500	13700	16500	17600	18700	W
Transformer-less, Ungrounded	Yes					
Maximum Input Voltage	950					Vdc
Nominal DC Input Voltage	750					Vdc
Maximum Input Current	17.5	21	22	23	23	Adc
Reverse-Polarity Protection	Yes					
Ground-Fault Isolation Detection	1MΩ Sensitivity					
Maximum Inverter Efficiency	98					%
European Weighted Efficiency	97.5	97.4	97.4	97.4	97.4	%
Nighttime Power Consumption	< 2.5					W
<b>ADDITIONAL FEATURES</b>						
Supported Communication Interfaces	RS485, RS232, Ethernet, Zigbee (optional)					
<b>STANDARD COMPLIANCE</b>						
Safety	IEC-62103 (EN50178), IEC-62109					
Grid Connection Standards	VDE 0126-1-1, VDE-AR-N-4105, AS-4777, RD-1663, DK 5940					
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC part15 class B					
RoHS	Yes					
<b>INSTALLATION SPECIFICATIONS</b>						
AC Output	Cable Gland - diameter 11-17					mm
DC Input	MC4					
Dimensions (HxWxD)	540 x 315 x 260					mm
Weight	32					kg
Operating Temperature Range	-20 - +60					°C
Cooling	Fan (user replaceable)					
Protection Rating	IP65 - Outdoor and Indoor					
Bracket Mounted (Bracket Provided)						

\* Higher input DC power may be installed; analyze yearly AC performance.



■ USA ■ Germany ■ Italy ■ France ■ Japan ■ China ■ Israel

**solar**edge

© SolarEdge Technologies, Inc. 2009-2012. All rights reserved. SOLAREEDGE, the SolarEdge logo, ARCHITECTS OF ENERGY and OPTIMIZED BY SOLAREEDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: 06/2012. V.02. Subject to change without notice.

DarsunSolar www.darsunsolar.pl tel. +48 697 161 842 e-mail:info@darsunsolar.pl