

# Change Your Energy Charge Your Life



## Compact Size & Easy Installation

The compact and lightweight nature of the RESU is world-class. It is designed to allow easy wall-mounted or floor-standing installation for both indoor and outdoor applications. The inverter connections have also been simplified, reducing installation time and costs.



## Powerful Performance


The new RESU series features industry-leading continuous power (4.2kW for RESU6.5) and DC round-trip efficiency (95%). LG Chem's L&S (Lamination & Stacking) technology provides durability ensuring 80% of capacity retention after 10 years.



## Proven Safety

LG Chem places the highest priority on safety and utilizes the same technology for its ESS products that has a proven safety record in its automotive battery. All products are fully certified in relevant global standards.

# RESU



# RESU

Change Your Energy, Charge Your Life

## 48V



Models		RESU3.3	RESU6.5	RESU10
Total Energy [kWh]		3.3	6.5	9.8
Usable Energy [kWh]		2.9	5.9	8.8
Capacity [Ah]		63	126	189
Nominal Voltage [V]		51.8	51.8	51.8
Voltage Range [V]		42.0~58.8	42.0~58.8	42.0~58.8
Max Power [kW]		3.0	4.2	5.0
Peak Power [kW] (for 3 sec.)		3.3	4.6	7.0
Dimension [W x H x D, mm]		452 x 401 x 120	452 x 654 x 120	452 x 483 x 227
Weight [kg]		31	52	75
Enclosure Protection Rating		IP55		
Communication		CAN 2.0 B		
Certificates	Cell	UL1642		
	Product	CE / RCM / TUV (IEC 62619) / UL1973		

Compatible Inverter Brands : SMA, SolaX, Sungrow, Schneider, Ingeteam, GoodWe, Redback, Victron Energy (As of 3Q. 2016, More brands to be added)

RESU PLUS



**RESU Plus is an expansion kit specially designed for 48V models of new RESU series.**  
**With RESU Plus, all 48V models can be cross-connected with each other.**

- Dimension: 385 x 240 x 65 (W x H x D, mm)
- Number of Expandable Battery Units: Up to 2EA
- IP55

## 400V



Models		RESU7H	RESU10H	
Total Energy [kWh]		7.0	9.8	
Usable Energy [kWh]		6.6	9.3	
Capacity [Ah]		63	63	
Voltage Range [V]		350~450	350~450	385~550
Max Power [kW]		3.5	5.0	
Peak Power [kW] (for 10 sec.)		5.0	7.0	
Dimension [W x H x D, mm]		744 x 692 x 206	744 x 907 x 206	
Weight [kg]		76	97	99.8
Enclosure Protection Rating		IP55		
Communication		RS485	RS485	CAN 2.0 B
Certificates	Cell	UL 1642		
	Product	TUV (IEC 62619) / CE	TUV (IEC 62619) / UL1973 / CE	